



MOTOREFFEKT : 5.5 KW
 LEVERINGSMENGDE : 21 L/MIN
 KONT.ARBEIDSTRYKK : 145 BAR
 INT. " : 170 "
 SPISSTRYKK : 190 "
 NETTO TANKVOLUM : 50 L

OLJEKVALITET:
 MINERALOLJE BASERT HYDRAULIKKOLJE,
 ISO VG32 ELLER 46

Pos.nr.	Ant.	Beskrivelse	Kode	UCN best.nr.
13	1	OMLØPSPLATE P-A,B-T	BS 505	6750500
12	1	TRYKK BEGR.VENT.		
11	1	FILTERPATRON	CR100 H	3468725
10	1	RETURFILTER 25µ	OMTF 85 HN	3468625
9	1	PUSTE-/PÅFYLLIGSFILTER	SES3-S	19726
8	1	SUGERØR Ø22		
7	1	GEV 15 LR3/8"		
6	1	SUGEFLENS Ø40-M22X1.5		2112835
5	1	TRYKKFLENS Ø30-3/8"		2112825
4	1	TANNHJ.PUMPE 15 CM³	20C15X 006	201100
3	1	FLEKS.KOBL. GR2/Ø38		2112814
2	1	MELLOMFL. GR.2/132		2112804
1	1	EL.MOTOR 5.5 KW 220/380V	T132-S4	2159920

Pos.nr.	Ant.	Beskrivelse	Kode	UCN best.nr.
---------	------	-------------	------	--------------

Dato	Konstr.Regnet	Godkjert	Målestokk
02.03.95	TGA		



Erstatning for	Erstattet av
----------------	--------------

Tegningsnummer
4-014

Henviisning	Beregning
-------------	-----------